

Post-bed, Bottom-feed Lockstitch Machine

Post-bed, Needle-feed Lockstitch Machine

PLH-981 (1-needle) PLH-982 (2-needle)

PLN-985 (1-needle)
PLN-986 (2-needle)

Well-tensed consistent seam quality. The machine demonstrates outstanding responsiveness when sewing heavy materials.

With a needle feed mechanism that operates in synchronization with the bottom feed, the machine produces beautiful seams free from slippage even when sewing slippery or hard-to-feed materials.









CONSISTENT SEAM QUALITY

With JUKI's unique slide thread take-up lever, feed mechanism, and vertical-axis hook, the machine provides well-tensed, neatly finished seams every time.





PLH-981 PLN-986

THE MACHINE HEAD STRUCTURE IS DESIGNED TO IMPROVE OPERABILITY.

- The stitch length can easily be adjusted with the stitch dial. Reverse-feed stitching is actuated by a simple press of the lever. The machine incorporates a large pulley that can be turned smoothly by hand.
- The face plate is designed to provide a clear view of the needle entry area and enable smooth thread feeding.





PLN-985 • 986

PLN-986

SPECIFICATIONS

	P. II. 0.04	DIII CCC	2111 222	DI II 00 /	
MODEL NAME	PLH-981	PLH-982	PLN-985	PLN-986	
	1-needle	2-needle	1-needle	2-needle	
Feed system	Bottor	n-feed	Needle-feed		
Max. sewing speed	2,500rpm				
Max. stitch length	4mm (normal/reverse feed)				
Needle bar stroke	36mm		33.4mm		
Needle gauge (mm)	1.2, 1.6, 2.0, 2.4 (standard)			2.0, 2.4 (standard)	
Lift of the presser foot	By hand: 7mm, By knee: 10mm		By hand: 6.5mm, By knee: 9mm		
Thread take-up	Slide type				
Hook	Vertical-axis hook				
Needle (at the time of delivery)	DP x 5 (#18) #16 ~ #21) #16~#21		
Thread	#40 ~ #8, B33 ~ B92, Nm=90/3 ~ 30/3				
Lubrication	By an oiler				
Lubricating oil	JUKI New Defrix Oil No.1 (equivalent to ISO VG7)				
Post height	178mm 179mm		mm		
Bed size	517mm × 178mm				
Weight of the machine head	36kg 40kg		kg		

GAUGE TABLE (2-NEEDLE TYPE)

PLH-982					
Needle gauge	Gauge set	Needle clamp	Needle guide	Throat plate	Feed dog
1.2mm	210-16357	210-17405	5 210-18908	210-16308	210-21100
1.6mm	210-16159	210-17403		210-16100	
2.0mm	210-16258			210-16209	210-21209
2.4mm (standard)	210-16050	210-17504	210-18809	210-16019	210-21308

PLN-986					
Needle gauge	Gauge set	Needle clamp	Needle guide	Throat plate	Feed dog
			FL.		
1.6mm	210-32156	210-17405	210-33006	210-32107	210-31109
2.4mm (standard)	210-32255	210-17504	210-33105	210-32206	210-31208



JUKI CORPORATION HEAD OFFICE

The environmental management system to promote and conduct ①the technological and technical research, the development and design of the products in which the environmental impact is considered.

zene conservation or me energy and resources, and the recycling in the research, development, design, distribution, sale and maintenance service of the industrial sewing machines, household sewing machines and industrial-use robots, etc. and in the purchase, distribution and sale of the household commodities including the healthcare products.



MARKETING & SALES H.Q.

8-2-1, KOKURYO-CHO, CHOFU-SHI, TOKYO 182-8655, JAPAN PHONE: (81) 3-3480-2357, 2358 FAX: (81) 3-3430-4909, 4914 http://www.juki.com

- * Specifications and appearance are subject to change without prior notice for improvement.
- * Read the instruction manual before putting the machine into service to ensure safety.

 * This catalog is printed on recycle paper.

WHEN YOU PLACE ORDERS

Please note when placing orders, that the model name should be written as follows:

• 1-needle, Bottom-feed

PLH981

• 2-needle, Bottom-feed

PLH	982B	
	Needle gauge	Code
	1.2mm	12
	1.6mm	16
	2.0mm	20
	2.4mm (standard)	24

• 1-needle, Needle-feed

PLN985

• 2-needle, Needle-feed

PLN986B

Needle gauge	Code
1.6mm	16
2.4mm (standard)	24

 $\bullet \mbox{To}$ order, please contact your nearest JUKI distributor.